

※ This document is a temporary specification which does not include whole information about the product.

※ This document is subject to be changed for approving product quality without notice.

SPECIFICATIONS	ITEM	LINE FILTER	Rev
	TNC SPEC NO	CH015030S	0

1. ELECTRICAL CHARACTERISTIC

NO	ITEM	TERMINAL	SPECIFICATION			REMARKS
1	RATED VOLTAGE	LINE TO LINE	AC 250V			
2	RATED CURRENT	START-FINISH	1.5A			
3	INDUCTANCE	START-FINISH	16KHz	3.0mH	+ 50%, -30%	HP-4194A 1V (20℃±5℃)
4	TEMPERATURE RISE	AT RATED CURRENT	55℃ MAX			
5	DC RESISTANCE	START-FINISH	79.0 mΩ MAX			HIOKI 3540 (20℃±5℃)
6	WITHSTANDING VOLTAGE	LINE TO LINE	AC 1,500V 1 MINUTE.			TOS-5101 CUT OFF CURRENT (5mA)



2. OPERATING TEMPERATURE RANGE

-25℃ TO +105℃ INCLUDING TEMPERATURE RISE.

3. KEEP TEMPERATURE RANGE

-10℃ ~ +60℃.

4. CIRCUIT DIAGRAM



Minimum PCB Piercing HOLE

#125 , WOLMUN-RI, PALTAN-MYEON,
HWASEONG-SI, KYUNGGI-DO, KOREA 445-914
TEL : 82+(0)313543160
FAX : 82+(0)313543156

TNC
TNC Co.,LTD

PAGE

1/2


※ This document is a temporary specification which does not include whole information about the product.
 ※ This document is subject to be changed for approving product quality without notice.

SPECIFICATIONS	ITEM	LINE FILTER	Rev
	TNC SPEC NO	CH015030S	0

5. WINDING SPECIFICATION

NO	TERMINAL		WIRE	TURNS	WINDING METHOD	UNBALANCE SPECIFICATION
	START	FINISH				
L1	1	3	UEW 0.4Φ	28 ±2Ts	HANDMADE	BETWEEN L1 AND L2 (0.2mH MAX)
L2	2	4				

6. SHAPE AND DIMENSION



DIMENSION	A	B	C	D
	15.0mm MAX	15.0mm MAX	8.0mm MAX	4.0 ± 1.0mm

#125 , WOLMUN-RI, PALTAN-MYEON,
 HWASEONG-SI, KYUNGGI-DO, KOREA 445-914
 TEL : 82+(0)313543160
 FAX : 82+(0)313543156

TNC
TNC Co.,LTD

PAGE

2/2